

WARRANTY EXCLUSIONS AND LIMITATION OF LIABILITY

IF THE USER DOES NOT ACCEPT THE FOLLOWING TERMS, THE USER SHOULD NOT USE THE SAFEAIR BADGES AND COLOR COMPARATORS.

Seller warrants that, for the lesser of one (1) year or the shelf-life provided on the Seller's product, its packaging or its literature, its products shall conform to the description of such products as provided on the Seller's product, its packaging or its literature. THIS WARRANTY IS EXCLUSIVE, AND SELLER MAKES NO OTHER WARRANTY, EXPRESS OR IMPLIED, INCLUDING ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR ANY PARTICULAR PURPOSE. Seller's warranties made in connection with this sale shall not be effective if Seller has determined, in its sole discretion, that Buyer has misused the products in any manner, has failed to use the products in accordance with safe industry standards and practices, or has failed to use the products in accordance with Seller's written operating instructions, or other instructions furnished by Seller to Buyer.

Seller's sole and exclusive liability and Buyer's exclusive remedy with respect to products to Seller's satisfaction to be defective or nonconforming shall be replacement of such products without charge or refund of the purchase price, in Seller's sole discretion, upon the return of such products in accordance with Seller's instructions. All claims must be brought within one (1) year of shipment, regardless of their nature.

SELLER SHALL NOT IN ANY EVENT BE LIABLE FOR INCIDENTAL, CONSEQUENTIAL OR SPECIAL DAMAGES OF ANY KIND RESULTING FROM ANY USE OR FAILURE OF THE PRODUCTS, EVEN IF SELLER HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGE INCLUDING, WITHOUT LIMITATION, LIABILITY FOR LOSS OF USE, LOSS OF WORK IN PROGRESS, DOWN TIME, LOSS OF REVENUE OR PROFITS, FAILURE TO REALIZE SAVINGS, LOSS OF PRODUCTS OF BUYER OR OTHER USE OF ANY LIABILITY OF BUYER TO A THIRD PARTY ON ACCOUNT OF SUCH LOSS, OR FOR ANY LABOR OR ANY OTHER EXPENSE, DAMAGE OR LOSS OCCASIONED BY SUCH PRODUCT INCLUDING PERSONAL INJURY OR PROPERTY DAMAGE UNLESS SUCH PERSONAL INJURY OR PROPERTY DAMAGE IS CAUSED BY SELLER'S GROSS NEGLIGENCE.

Warning: Keep out of reach of children, if ingested seek medical attention immediately.



2557 Production Rd.
Virginia Beach, VA 23454
Phone: (757) 431-2260 Fax: (757) 216-6209
e-mail: customerservice@morphtec.com

©1997, Morphix Technologies®
All rights reserved
Publication Number: KM1-7A.5-0606
US Patent Number: 6,284,198



Operating Instructions For Chlorine Monitor (Part Number: 382009)

Technical Summary

Physical Specifications:

| | |
|-------------------------|------------------------------------|
| Dimensions | (74 ± 1 mm) x (41 ± 1 mm) x (1 mm) |
| Weight | 1.5 g |
| Refrigerated shelf life | 2 years |
| Color change | yellow to orange |

Sampling Parameters:

| | |
|-------------------------------------|-------------------|
| Exposure dose: | |
| Badge | 0.18 ppm·hr |
| Badge with color comparator | 0.03 - 3.0 ppm·hr |
| Minimum detectable limit (8 hours) | 0.023 ppm |
| Maximum recommended sampling time | 48 hours |
| Minimum recommended sampling time | 15 minutes |
| Relative humidity range | 30% - 90% |
| Face velocity range | 10 - 150 cm/sec |
| Temperature range | 60°F - 91°F |
| Light effect - UV (direct sunlight) | no effect |
| Light effect - visible | no effect |
| Color stability | 4 weeks |

Applications:

The SafeAir chlorine badge may be used for personnel or area monitoring for exposure times ranging from 15 minutes to 48 hours. For higher resolution, the SafeAir chlorine badge may be used in conjunction with the SafeAir chlorine color comparator (part number: 383010).

Cross Interferences:

Bromine and iodine react with approximately the same sensitivity. Hydrogen chloride and hydrochloric acid at concentrations greater than 1 ppm can seriously impair the performance of the chlorine badge. No other interferences are known.

Introduction

Chlorine is a greenish-yellow gas with a pungent, irritating odor. Generally, chlorine is a potent respiratory system irritant. Mild exposures to chlorine cause burning of eyes, nose and mouth. Exposure to concentrations as high as 1000 ppm is likely to be fatal after a few deep breaths. The OSHA PEL for chlorine is 1 ppm (ceiling), whereas the NIOSH REL is 0.5ppm (ceiling).

Chlorine is an important chemical commodity widely used in the production of safe drinking water. It is also extensively used in the production of paper products, dyestuffs, textiles, petroleum products, chlorinated solvents, etc.

Principle of Operation

The SafeAir chlorine badge is a monitoring system designed to indicate the presence of chlorine at concentrations below the permissible exposure limit. The SafeAir chlorine badge detects the presence of chlorine by forming a color change in the shape of an exclamation mark inside the triangle. This indication is produced by a color-forming reaction which occurs when chlorine reacts with a flat indicator layer.

Operating Instructions

1. Remove the pouch from the refrigerator and allow it to warm to room temperature.
2. Remove the badge from its protective pouch.
3. For personnel monitoring, attach the badge near the user's breathing zone (i.e. the collar) with the front side exposed to the surrounding atmosphere.
4. For area monitoring, attach the badge to a stand and mount in a centralized area with the front side exposed to the surrounding atmosphere.
5. The exclamation mark appears within the triangle when chlorine is present. Please note that the exclamation mark will appear underneath the printed exposure dose (sensitivity).
6. To obtain the average concentration, divide the exposure dose (ppm-hr) by the exposure time in hours (hr).

Storage

The SafeAir chlorine badge should be refrigerated in its sealed bag at all times.

Benefits

1. Accurate Detection: The SafeAir chlorine badge is designed to react selectively with chlorine with minimum interference from other substances.
2. Applications: The SafeAir badge may be used for personnel screening and for area monitoring or area mapping.
3. Ease of Use: The SafeAir badge is a direct-read device that gives immediate, on-site results.

Other Available Monitors

1. SafeAir Badges:

| | | |
|---------------------------|-------------------|----------------|
| Ammonia | Hydrazine | Phosgene |
| Aromatic Isocyanates | Hydrogen Chloride | Phosgene Dura |
| Carbon Monoxide | Hydrogen Sulfide | Phosgene Medi |
| Chlorine/Chlorine Dioxide | Mercury | Sulfur Dioxide |
| Formaldehyde | Ozone | |
2. SafeAir Color Comparators:

| | | |
|-----------------------------|---------------------|------------------|
| Chloroformates ¹ | Phosgene | Phosgene Medi |
| Hydrazine | Phosgene ext. range | TDI ² |
| Hydrogen Chloride | Phosgene Dura | |

If you require SafeAir monitors for a chemical hazard not listed, please contact Morphix Technologies® for a free compound consultation at (800) 808-2234.

¹ To be used with the SafeAir phosgene badges

² To be used with the SafeAir aromatic isocyanates badges