Copper CHEMets[®] Kit

K-3510/R-3510: 0 - 1 & 1 - 10 ppm

Safety Information

Read ŠDS (available at www.chemetrics.com) before performing this test procedure. Wear safety glasses and protective gloves.

Test Procedure


- 1. Fill the sample cup to the 25 mL mark with the sample to be tested (fig 1).
- 2. Place the CHEMet ampoule, tip first, into the sample cup. Snap the tip. The ampoule will fill leaving a bubble for mixing (fig 2).
- 3. To mix the ampoule, invert it several times, allowing the bubble to travel from end to end.
- 4. Dry the ampoule and wait **2 minutes** for color development.
- 5. Obtain a test result using the appropriate comparator.
 - a. Low Range Comparator (fig. 3): Place the ampoule, flat end first, into the comparator. Hold the comparator up toward a source of light and view from the bottom. Rotate the comparator until the best color match is found.
 - b. **High Range Comparator (fig. 4):** Place the ampoule between the color standards until the best color match is found.

The Copper CHEMets^{®1} test method employs the bathocuproine chemistry.² In a neutral solution, cuprous ions react with bathocuproine (2,9-dimethyl-4,7-diphenyl-1,10-phenanthrolinedisulfonic acid, disodium salt) to form an orange colored chelate in direct proportion to the copper concentration.

This test method is applicable to drinking water, surface water, groundwater, wastewaters and seawater. For seawater analysis wait **1 minute** for color development.

1. CHEMets is a registered trademark of CHEMetrics, Inc. U.S. Patent No. 3,634,038

2. APHA Standard Methods, 22nd ed., Method 3500-Cu C - 1999






www.chemetrics.com 4295 Catlett Road, Midland, VA 22728 U.S.A. Phone: (800) 356-3072; Fax: (540) 788-4856 E-Mail: orders@chemetrics.com

Simplicity in Water Analysis

Mar: 18, Rev. 7








Figure 4